

Größe	Reifen		Felgen ⁷⁾ (Messfelge fett)	TL-Ventil (Schlauch und Ventil) ⁷⁾	Reifenmaße				neu		Halbmesser stat. +/- 2 % (mm)	Abrollumfang + 1,5 % - 2,5 % (mm)
	PR	Betriebskennung ⁶⁾			Normwert max im Betrieb ⁸⁾		Außen-Ø		Breite	Außen-Ø		
					Breite Standard	Spezial	Standard	Spezial				
16 Zoll												
215/75 R 16 C	8	113/111 R	5 ½ J	TR 600 XHP, TR 602 HP, 40 MS	220	740	748	211	728	332	2206	
		116/114 N	6 J		225			216				
	116/114 R	6 ½ J	230		221							
		7 J	235		226							
225/75 R 16 C	8	116/114 R	6 J	TR 600 XHP, TR 602 HP, 40 MS	232	758	764	223	744	338	2254	
		116/114 N (110 S)	6 ½ J		237			228				
		116/114 R (118/116 P)	7 J		242			233				
					40 MS							
	10	118/116 R										
		121/120 N										
		121/120 N (118 R)										
		121/120 R										
		121/120 R (118/116 S)										
225/75 R 16 CP	8	116 R		TR 600 XHP, TR 602 HP, 40 MS								
215/70 R 16 C	6	108/106 S	5 ½ J	43 GS 11.5	220	720	726	211	708	324	2145	
		108/106 T	6 J		225			216				
			6 ½ J		230			221				
			7 J		235			226				
195/65 R 16 C	6	100/98 T	5 ½ J	TR 600 XHP, TR 602 HP	204	670	676	196	660	305	2000	
	8	104/102 R	6 J		209			201				
		104/102 R (100 R)										
		104/102 T										
		104/102 T (100 T)										

PR	Last-Index	Radan-ordnung ⁹⁾	Tragfähigkeit (kg) pro Achse bei Luftdruck (bar)													GSY und Referenz-geschwin-digkeit (km/h)
			3,0	3,25	3,5	3,75	4,0	4,25	4,5	4,75	5,0	5,25	5,5	5,75	6,0	
8	113	E	1590	1700	1800	1905	2005	2105	2205	2300						N 140 R 170
	111	Zw	3020	3220	3415	3610	3800	3990	4175	4360						
	10	116	E	1600	1705	1805	1910	2010	2110	2210	2310	2405	2500			
		114	Zw	3015	3215	3410	3605	3795	3985	4170	4355	4540	4720			
	10	116	VA E	1600	1705	1805	1910	2010	2110	2210	2310	2405	2500			
		116	HA E	1600	1705	1805	1910	2010	2110	2210	2310	2405	2500	2500	2500	
	114	HA Zw	3015	3215	3410	3605	3795	3985	4170	4355	4540	4720	4720	4720		
8	116	E	1730	1845	1960	2070	2180	2285	2395	2500					N 140 R 170 (R 170) (S 180) (P 150)	
	114	Zw	3270	3485	3695	3905	4115	4320	4520	4720						
	116	E	1730	1845	1960	2070	2180	2285	2395	2500						
	114	Zw	3270	3485	3695	3905	4115	4320	4520	4720						
	110	E	1605	1710	1815	1920	2020	2120								
	116	E	1730	1845	1960	2070	2180	2285	2395	2500						
	114	Zw	3270	3485	3695	3905	4115	4320	4520	4720						
	118	E	1685	1800	1910	2015	2125	2230	2335	2435	2540	2640				
	116	Zw	3195	3410	3615	3820	4020	4220	4420	4615	4810	5000				
	10	118	E	1685	1800	1910	2015	2125	2230	2335	2435	2540	2640			
		116	Zw	3195	3410	3615	3820	4020	4220	4420	4615	4810	5000			
		121	E	1725	1835	1950	2060	2170	2275	2385	2490	2595	2695	2800		2900
		120	Zw	3330	3550	3765	3980	4190	4395	4605	4805	5010	5205	5405		5600
		121	E	1725	1835	1950	2060	2170	2275	2385	2490	2595	2695	2800		2900
		120	Zw	3330	3550	3765	3980	4190	4395	4605	4805	5010	5205	5405		5600
		118	E	1685	1800	1910	2015	2125	2230	2335	2435	2540	2640			
		121	E	1725	1835	1950	2060	2170	2275	2385	2490	2595	2695	2800		2900
		120	Zw	3330	3550	3765	3980	4190	4395	4605	4805	5010	5205	5405		5600
118		E	1685	1800	1910	2015	2125	2230	2335	2435	2540	2640				
116	Zw	3195	3410	3615	3820	4020	4220	4420	4615	4810	5000					
8	116	VA E	1730	1845	1960	2070	2180	2285	2395	2500						
	116	HA E	1540	1640	1740	1840	1940	2035	2130	2225	2315	2410	2500			
	1,85x116	HA Zw	3200	3415	3625	3830	4030	4230	4430	4625						
6	108	E	1675	1785	1895	2000								S 180 T 190		
	106	Zw	3180	3390	3595	3800										
6	100	E	1340	1425	1515	1600								R 170 T 190		
	98	Zw	2510	2675	2840	3000										
8	104	E	1245	1330	1410	1490	1570	1645	1725	1800						
	102	Zw	2355	2510	2665	2815	2965	3110	3255	3400						
	100	E	1340	1425	1515	1600										

* (Ventile) siehe Seite 76

Fußnoten siehe Ausklappseite am Umschlag